



1. *Template for connecting a channel with a height of 260 mm
2. Dimensions for reference
3. Delivery and packaging are carried out in accordance with the terms of the contract
4. The manufacturer reserves the right, without notice to the consumer, to make changes to the design of the products for improvement of their technological and operational parameters, which will not affect the quality and properties of the product
5. Deviation of the actual weight of the nominal can be up to 10%.

Nr	Article	Name	Weight, kg
1	042871334	Concrete Sand Trap Pro DN150 H500 with Cast Iron Grate D400	67.3
2	042871334-K	Concrete Sand Trap Pro DN150 H500 with basket with Cast Iron Grate D400	69
3	042871334-P160	Concrete Sand Trap Pro DN150 H500 outlet 160 with Cast Iron Grate D400	66.3
4	042871334-P160-K	Concrete Sand Trap Pro DN150 H500 with basket outlet 160 with Cast Iron Grate D400	68



UNLESS OTHERWISE SPECIFIED: DIMENSIONS ARE IN MILLIMETERS		FINISH:		DEBURR AND BREAK SHARP EDGES		DO NOT SCALE DRAWING		REVISION	
SURFACE FINISH: TOLERANCES: ISO 2768 - C									
LINEAR:									
ANGULAR:									
DRAWN		Kyselytsia		SIGNATURE		DATE		13.09.22	
CHK'D		Kharambura							
APPV'D		Malynovskiy							
MFG									
Q.A									
				MATERIAL:		Concrete, Cast Iron		TITLE: Concrete Sand Trap Pro DN150 H500 with Cast Iron Grate D400	
				WEIGHT: kg				ARTICLE: 042871334	
								A3	
								SCALE:1:5	
								SHEET 1 OF 1	